

SAFETY DATA SHEET

TERRA NOVA CRUDE



000003000793

Version 5.0

Revision Date 2019/05/03

Print Date 2019/05/03

SECTION 1. IDENTIFICATION

Product name : TERRA NOVA CRUDE

Synonyms : Crude Oil

Manufacturer or supplier's details

SUNCOR ENERGY INC.
P.O. Box 2844, 150 - 6th Avenue South-West
Calgary Alberta T2P 3E3
Canada

Emergency telephone number : Suncor Energy: +1 403-296-3000;
Canutec Transportation: 1-888-226-8832 (toll-free) or 613-996-6666;
Poison Control Centre: Consult local telephone directory for emergency number(s).

Recommended use of the chemical and restrictions on use

Recommended use : Raw product for oil refineries to produce fuels and other petroleum based organic products.

Prepared by : Product Safety: +1 905-804-4752

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Colour	Light to dark brown, may vary with crude sources.
Odour	Mild petroleum oil like. "Rotten egg" if H ₂ S present, but odour is an unreliable warning, since it may deaden the sense of smell.

GHS Classification

Flammable liquids : Category 2

Skin irritation : Category 2

Eye irritation : Category 2B

Germ cell mutagenicity : Category 1B

Carcinogenicity : Category 1A

Reproductive toxicity : Category 2

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

SAFETY DATA SHEET

TERRA NOVA CRUDE



000003000793

Version 5.0

Revision Date 2019/05/03

Print Date 2019/05/03

Specific target organ toxicity
- repeated exposure : Category 2

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : Highly flammable liquid and vapour.
May be fatal if swallowed and enters airways.
Causes skin and eye irritation.
May cause drowsiness or dizziness.
May cause genetic defects.
May cause cancer.
Suspected of damaging fertility or the unborn child.
May cause damage to organs (Liver, Bone, thymus) through prolonged or repeated exposure.

Precautionary statements : **Prevention:**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.
Ground and bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting equipment.
Use non-sparking tools.
Take action to prevent static discharges.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Wash skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
IF SWALLOWED: Immediately call a POISON CENTER/doctor.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/ attention.
Do NOT induce vomiting.
If skin irritation occurs: Get medical advice/ attention.
If eye irritation persists: Get medical advice/ attention.
Take off contaminated clothing and wash it before reuse.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

SAFETY DATA SHEET

TERRA NOVA CRUDE



000003000793

Version 5.0

Revision Date 2019/05/03

Print Date 2019/05/03

Storage:

Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects

Primary Routes of Entry : Eye contact
Ingestion
Inhalation
Skin contact

Aggravated Medical Condition : None known.

Other hazards

None known.

IARC

Group 1: Carcinogenic to humans

Benzene 71-43-2

Group 2B: Possibly carcinogenic to humans

Ethylbenzene 100-41-4

ACGIH

Confirmed human carcinogen

Benzene 71-43-2

Confirmed animal carcinogen with unknown relevance to humans

Ethylbenzene 100-41-4

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration
petroleum	8002-05-9	100 %
xylene	1330-20-7	0.1 - 1 %

SAFETY DATA SHEET

TERRA NOVA CRUDE



000003000793

Version 5.0

Revision Date 2019/05/03

Print Date 2019/05/03

toluene	108-88-3	0.1 - 1 %
1,2,4-trimethylbenzene	95-63-6	0.1 - 0.5 %
ethylbenzene	100-41-4	0.1 - 0.5 %
benzene	71-43-2	0.1 - 0.5 %
hydrogen sulphide	7783-06-4	< 0.02 %

All above concentrations are in percent by weight.

SECTION 4. FIRST AID MEASURES

- If inhaled : Move to fresh air.
Artificial respiration and/or oxygen may be necessary.
Seek medical advice.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Wash skin thoroughly with soap and water or use recognized skin cleanser.
Wash clothing before reuse.
Seek medical advice.
- In case of eye contact : Remove contact lenses.
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Obtain medical attention.
- If swallowed : Rinse mouth with water.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Never give anything by mouth to an unconscious person.
Seek medical advice.
- Most important symptoms and effects, both acute and delayed : Respiratory, skin and eye irritation; nausea; cancer.
Exposure to very high levels of hydrogen sulphide (> 500 ppm) will result in unconsciousness and death.
In high doses hydrogen sulphide may produce pulmonary edema and respiratory depression or paralysis.
Symptoms of hydrogen sulphide overexposure include respiratory tract irritation and shortness of breath.
Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.
- Notes to physician : Treat symptomatically.
Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Dry chemical
Carbon dioxide (CO₂)
Water fog.
Foam

SAFETY DATA SHEET

TERRA NOVA CRUDE



000003000793

Version 5.0

Revision Date 2019/05/03

Print Date 2019/05/03

-
- | | |
|---|---|
| Unsuitable extinguishing media | : Do NOT use water jet. |
| Specific hazards during fire-fighting | : If the product release cannot be shut off safely, allow the product to burn itself out.
Cool closed containers exposed to fire with water spray. |
| Hazardous combustion products | : Carbon oxides (CO, CO ₂), nitrogen oxides (NO _x), sulphur oxides (SO _x), sulphur compounds (H ₂ S), smoke and irritating vapours as products of incomplete combustion. |
| Further information | : Prevent fire extinguishing water from contaminating surface water or the ground water system. |
| Special protective equipment for firefighters | : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear. |
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : For personal protection see section 8.
Ensure adequate ventilation.
Evacuate personnel to safe areas.
Material can create slippery conditions. |
| Environmental precautions | : If the product contaminates rivers and lakes or drains inform respective authorities. |
| Methods and materials for containment and cleaning up | : Prevent further leakage or spillage if safe to do so.
Remove all sources of ignition.
Soak up with inert absorbent material.
Non-sparking tools should be used.
Ensure adequate ventilation.
Contact the proper local authorities. |
-

SECTION 7. HANDLING AND STORAGE

- | | |
|-------------------------|--|
| Advice on safe handling | : For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Use only with adequate ventilation.
In case of insufficient ventilation, wear suitable respiratory equipment.
Take precautionary measures against static discharges.
Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity.
Keep away from open flames, hot surfaces and sources of ignition.
Do not use sparking tools.
Avoid contact with skin, eyes and clothing.
Do not ingest.
Keep container closed when not in use.
Hydrogen sulphide may accumulate in enclosed spaces.
Open tank car hatches with caution. |
|-------------------------|--|

SAFETY DATA SHEET

TERRA NOVA CRUDE



000003000793

Version 5.0

Revision Date 2019/05/03

Print Date 2019/05/03

Conditions for safe storage : Store in original container.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Keep in a dry, cool and well-ventilated place.
 Keep in properly labelled containers.
 To maintain product quality, do not store in heat or direct sunlight.
 Keep away from sources of ignition - No smoking.
 Hydrogen sulphide may be released and collect in the vapor space of process vessels and storage tanks.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
xylene	1330-20-7	STEL	150 ppm 651 mg/m ³	CA AB OEL
		TWA	100 ppm 434 mg/m ³	CA AB OEL
		TWAEV	100 ppm 434 mg/m ³	CA QC OEL
		STEV	150 ppm 651 mg/m ³	CA QC OEL
		TWA	100 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
toluene	108-88-3	TWA	50 ppm 188 mg/m ³	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	50 ppm 188 mg/m ³	CA QC OEL
		TWA	20 ppm	ACGIH
ethylbenzene	100-41-4	TWA	100 ppm 434 mg/m ³	CA AB OEL
		STEL	125 ppm 543 mg/m ³	CA AB OEL
		TWA	20 ppm	CA BC OEL
		STEV	125 ppm 543 mg/m ³	CA QC OEL
		TWAEV	100 ppm 434 mg/m ³	CA QC OEL
		TWA	20 ppm	ACGIH
benzene	71-43-2	TWA	0.5 ppm 1.6 mg/m ³	CA AB OEL
		STEL	2.5 ppm 8 mg/m ³	CA AB OEL

SAFETY DATA SHEET

TERRA NOVA CRUDE



000003000793

Version 5.0

Revision Date 2019/05/03

Print Date 2019/05/03

		TWA	0.5 ppm	CA BC OEL
		STEL	2.5 ppm	CA BC OEL
		TWA	0.5 ppm	CA ON OEL
		STEL	2.5 ppm	CA ON OEL
		TWAEV	1 ppm 3 mg/m ³	CA QC OEL
		STEV	5 ppm 15.5 mg/m ³	CA QC OEL
		TWA	0.5 ppm	ACGIH
		STEL	2.5 ppm	ACGIH
hydrogen sulphide	7783-06-4	TWA	10 ppm 14 mg/m ³	CA AB OEL
		Ceiling	15 ppm 21 mg/m ³	CA AB OEL
		Ceiling	10 ppm	CA BC OEL
		TWA	10 ppm	CA ON OEL
		STEL	15 ppm	CA ON OEL
		TWAEV	10 ppm 14 mg/m ³	CA QC OEL
		STEV	15 ppm 21 mg/m ³	CA QC OEL
		TWA	1 ppm	ACGIH
		STEL	5 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI

Engineering measures : Use only in well-ventilated areas.
Ensure that eyewash station and safety shower are proximal to the work-station location.
Adequate ventilation to ensure that Occupational Exposure Limits are not exceeded.

Personal protective equipment

Respiratory protection : Concentration in air determines protection needed.
Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

SAFETY DATA SHEET

TERRA NOVA CRUDE



000003000793

Version 5.0

Revision Date 2019/05/03

Print Date 2019/05/03

Filter type	: A NIOSH-approved positive-pressure, air-supplied respirator or self-contained breathing apparatus may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.
Hand protection Material	: polyvinyl alcohol (PVA), Viton(R). Consult your PPE provider for breakthrough times and the specific glove that is best for you based on your use patterns. It should be realized that eventually any material regardless of their imperviousness, will get permeated by chemicals. Therefore, protective gloves should be regularly checked for wear and tear. At the first signs of hardening and cracks, they should be changed.
Remarks	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Eye protection	: Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Protective measures	: Wear suitable protective equipment.
Hygiene measures	: Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash face, hands and any exposed skin thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: Light to dark brown, may vary with crude sources.
Odour	: Mild petroleum oil like. "Rotten egg" if H ₂ S present, but odour is an unreliable warning, since it may deaden the sense of smell.
Odour Threshold	: No data available
pH	: No data available
Melting point	: -10 °C (14 °F)
Initial boiling point and boiling range	: 47.7 °C (117.9 °F)
Decomposition temperature	No data available
Flash point	: < -35 °C (< -31 °F) Method: closed cup

SAFETY DATA SHEET

TERRA NOVA CRUDE



000003000793

Version 5.0

Revision Date 2019/05/03

Print Date 2019/05/03

Auto-Ignition Temperature	:	No data available
Evaporation rate	:	No data available
Flammability	:	Easily ignites under almost all normal temperature conditions. Extremely flammable in presence of open flames, sparks, shocks, heat, oxidizing materials. Vapours are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks), and may travel considerable distance to sources of ignition and flash back.
Upper explosion limit	:	15 %(V)
Lower explosion limit	:	0.6 %(V)
Vapour pressure	:	37.4 kPa Method: ASTM D6377
Relative vapour density	:	No data available
Relative density	:	0.8554
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	No data available
Viscosity		
Viscosity, kinematic	:	6 cSt (40 °C / 104 °F)

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Hazardous polymerisation does not occur.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Reactive with oxidising agents, corrosives and interhalogens.
Hazardous decomposition products	:	May release CO _x , NO _x , SO _x , H ₂ S, smoke and irritating vapours when heated to decomposition.

SAFETY DATA SHEET

TERRA NOVA CRUDE



000003000793

Version 5.0

Revision Date 2019/05/03

Print Date 2019/05/03

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact
Ingestion
Inhalation
Skin contact

Acute toxicity

Product:

Acute oral toxicity : Remarks: Based on available data, the classification criteria are not met.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria are not met.

Acute dermal toxicity : Remarks: Based on available data, the classification criteria are not met.

Components:

petroleum:

Acute oral toxicity : LD50 (Mouse): > 4,300 mg/kg,

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

xylene:

Acute oral toxicity : LD50 (Rat): 4,300 mg/kg,

Acute inhalation toxicity : LC50 (Rat): 5000 ppm
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 1,700 mg/kg,

toluene:

Acute oral toxicity : LD50 (Rat): 5,580 mg/kg,

Acute inhalation toxicity : LC50 (Rat): 7585 ppm
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): 12,125 mg/kg,

1,2,4-trimethylbenzene:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): 18 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 3,160 mg/kg,

SAFETY DATA SHEET

TERRA NOVA CRUDE



000003000793

Version 5.0

Revision Date 2019/05/03

Print Date 2019/05/03

ethylbenzene:

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg,
Acute inhalation toxicity : LC50 (Rat): 4000 ppm
Exposure time: 4 h
Test atmosphere: vapor
Acute dermal toxicity : LD50 (Rabbit): 15,380 mg/kg,

benzene:

Acute oral toxicity : LD50 (Rat): 2,990 mg/kg,
Acute inhalation toxicity : LC50 (Rat): 13700 ppm
Exposure time: 4 h
Test atmosphere: vapour
Acute dermal toxicity : LD50 (Rabbit): > 8,240 mg/kg,

hydrogen sulphide:

Acute inhalation toxicity : LC50 (Rat): 444 ppm
Exposure time: 4 h
Test atmosphere: gas

Skin corrosion/irritation

Product:

Remarks: Causes skin irritation.

Serious eye damage/eye irritation

Product:

Remarks: Irritating to eyes.

Respiratory or skin sensitisation

Product:

Remarks: Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

Germ cell mutagenicity-
Assessment : May cause genetic defects.

Carcinogenicity

Product:

Carcinogenicity - As-
sessment : May cause cancer.

SAFETY DATA SHEET

TERRA NOVA CRUDE



000003000793

Version 5.0

Revision Date 2019/05/03

Print Date 2019/05/03

Reproductive toxicity

Product:

Reproductive toxicity - Assessment Suspected of damaging fertility or the unborn child.

STOT - single exposure

Product:

Remarks: May cause drowsiness or dizziness.

STOT - repeated exposure

Product:

Target Organs: Liver, Bone, thymus
Remarks: May cause damage to organs through prolonged or repeated exposure.

No data available

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae : Remarks: No data available

Toxicity to bacteria : Remarks: No data available

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

SAFETY DATA SHEET

TERRA NOVA CRUDE



000003000793

Version 5.0

Revision Date 2019/05/03

Print Date 2019/05/03

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Offer surplus and non-recyclable solutions to a licensed disposal company.
Waste must be classified and labelled prior to recycling or disposal.
Send to a licensed waste management company.
Dispose of as hazardous waste in compliance with local and national regulations.
Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1267
Proper shipping name : Petroleum crude oil
Class : 3
Packing group : II
Labels : Class 3 - Flammable Liquid
Packing instruction (cargo aircraft) : 364

IMDG-Code

UN number : UN 1267
Proper shipping name : PETROLEUM CRUDE OIL

Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

National Regulations

TDG

UN number : UN 1267
Proper shipping name : PETROLEUM CRUDE OIL

Class : 3
Packing group : II
Labels : 3
ERG Code : 128

SAFETY DATA SHEET

TERRA NOVA CRUDE



000003000793

Version 5.0

Revision Date 2019/05/03

Print Date 2019/05/03

Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

DSL On the inventory, or in compliance with the inventory
TSCA All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

SECTION 16. OTHER INFORMATION

For Copy of SDS : Internet: www.petro-canada.ca/msds
Canada-wide: telephone: 1-800-668-0220; fax: 1-800-837-1228
For Product Safety Information: 1 905-804-4752

Prepared by : Product Safety: +1 905-804-4752

Revision Date : 2019/05/03

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.